

# FLEXIBLE FLOOR BUNDING

EXTRA BUND CAPACITY IN SMALL AREAS  
'NO BOUNCE' DRIVE OVER BUNDING



Product	Length	Width	Height
Flexible Floor Bunding	10m	245mm	75mm
Flexible Floor Bunding	25m	245mm	75mm
Flexible Floor Bunding 90° corner	500mm	245mm	75mm

## APPLICATION EXAMPLES:

- Warehouses, doorways and access points
- Hazardous liquid storage areas
- Work shops

Flexible Floor Bunding is manufactured from purpose extruded foam encased in heavy-duty PVC. The triangular profile collapses down as vehicles drive over it and then springs back to shape after the vehicle passes. This allows for a steady pass for forklifts without compromising their load as they cross the banded section.

This bund type is manufactured in a standard 75mm height which generates greater containment capacity in the case of small banded areas.


Manufactured using heavy duty, high visibility 900gsm PVC. The material has very good chemical resistance and durability.

Installation kit available. For each 10m length you will require:

- 20m of aluminium flat bar or rubber insertion strip
- 50 x Countersunk 6mm hole – 35mmD concrete fasteners
- 4x tubes of adhesive sealant

Before purchasing floor bunding ensure you check ground clearance of forklifts. In some cases this bunding can be removed and re-installed if required.

 renew solutions

 1300 912 949

 sales@renewsolutions.com.au

 renewsolutions.com.au